





Introduction

Mission loudspeakers have always been afforded the highest respect, both in critical listening tests and for its iconic style.

Aiming for perfection in musical performance and in design aesthetic, the new Mission 76 Series is capable of achieving a level of sonic accuracy and realism. Competent and composed throughout an entire spectrum of music genres, the Mission 76 Series offer not only insight and clarity to recordings, but also deliver an embracing sense of musicality.

Cone Dynamics

Mission has constantly been pushing the frontiers of acoustic research further by using the latest advances in polymer technology in producing its own stronger, lighter and faster cone material called 'Parawave' – resulting from years of in-depth research into the properties of Aramid Fibres, which are man-made polymers with exceptional tensile strength that is 5 times stronger than the equivalent weight of steel, and how they can be used to create a cone that exhibits near perfect linear pistonic motion over its entire frequency range, whilst retaining speed and accuracy.











| Mission | 76 | Series |
|---------|----|--------|
|---------|----|--------|

| 111331011 70 001103 | | | | | |
|----------------------------|---------------------|-------------------|-------------------|-------------------|-------------------|
| Product Name: | 760 | 762 | 764 | 766 | 76C |
| Enclosure Type: | 2-way reflex | 2-way reflex | 3-way reflex | 3-way reflex | 2-way reflex |
| Components - bass | | | 150mm | 200mm | |
| - bass/mid | 130mm | 150mm | 130mm | 150mm | 130mm x 2 |
| - tweeter | 25mm | 25mm | 25mm | 25mm | 25mm |
| Frequency + /-3dB | 45 Hz - 20 kHz | 41 Hz - 20 kHz | 35 Hz - 20 kHz | 30 Hz - 20 kHz | 70 Hz -20 kHz |
| (boundary) | | | | | |
| Sensitivity SPL/M @ 2.83V: | 86 dB | 87 dB | 87 dB | 88 dB | 88 dB |
| Impedance: | 8 Ohms compatible | 8 Ohms compatible | 8 Ohms compatible | 8 Ohms compatible | 8 Ohms compatible |
| | (min 5.6 Ohms) | (min 5.6 Ohms) | (min 4 Ohms) | (min 4 Ohms) | (min 5.6 Ohms) |
| Recommended Amplifier: | 50 - 150W | 50 - 175W | 50 - 200W | 50 - 200W | 50 - 200W |
| Volume: | 6 litres | 10.7 litres | 19.3 litres | 33.9 litres | 8.2 litres |
| Frequency Fb | 55 hz | 45 hz | 40 hz / 75 hz | 35 hz / 70 hz | 55 hz |
| Crossover frequency | 2.0khz | 1.7khz | 250hz / 2.0khz | 220hz / 1.7khz | 2.0khz |
| Dimensions(H x W x D): mm | 300 x 170 x 280 | 360 x 206 x 330 | 880 x 170 x 315 | 1035 x 206 x 370 | 170 x 395 x 290 |
| Real Wood Finishes: | black ash | black ash | black ash | black ash | black ash |
| | cherry | cherry | cherry | cherry | cherry |
| | beech | beech | beech | beech | beech |
| | rosewood | rosewood | rosewood | rosewood | rosewood |
| Included Accessories: | | | | | |
| Optional Accessories: | Wall Bracket (Pair) | | | | |
| | Stand (Pair) | Stand (Pair) | | | |
| Package Quantity: | pair | pair | single | single | single |
| Net. Weight | 10.4 | 14.6 | 16 | 23.2 | 8.3 |
| Carton Size H x W x D | 384*490*351 | 443*517*403 | 954*383*274 | 1109*429*335 | 361*462*274 |
| Gross Weight | 12.1 | 16.7 | 18.7 | 26.4 | 9.6 |



IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU, UK

Tel: +44(0)1480 447700 Fax: +44(0)1480 431767 http://www.mission.co.uk

The information in this leaflet is subject to change without prior notice. All Rights Reserved © IAG Group Ltd.

Mission is a member of the International Audio Group. CODE:106-MI76090001







